

Small Part Spray Booth Profi A 1700, A 2500



Small Part Spray booth A1700

GESCHA Small Part Spray Booth Profi A1700, A2500

With patented metal front cover (ex-zones: 1 and 2)

The indirect GESCHA extraction system is the heart of the small part spray booth Profi type A, as where the **patented metal front cover** and the integrated suction jet are individually adjustable and allow direct and precise surface work on your parts. The double filter system allows a thorough and environment protective cleaning of the air.

The **high performance fan** is direct driven by an explosion proof motor (ex-zones: 1 and 2). The extraction of the air is straight forward as well as down through the integrated grates on the work area.


This unit is **available in two sizes**. Special editions are available upon request. You have the option to order this unit with complete electric wiring and motor protection as well as ordering replacement filters.



Small Part Spray Booth A1700/A2500 with optional front piece



Patented GESCHA extraction system




Side view

New
Extraction
through the
gratings



Fast filter replacement



Front view

* On type a 2500 with extern blower

Small Part Spray Booth Profi A 1700, A 2500									
	Art.-No.	Description	Explosion proof motor (50Hz)	Exhaust air free blowing (m³/h)	Exhaust duct Ø (mm)	Filter area (m²)	AB (mm)	AI (mm)	
	45150-A1700-1	Small part spray booth A1700	1,1 kW ~ 400V	3400	250	2,5	1760	1710	
	45150-A2500-1	Small part spray booth A2500	1,1 kW ~ 400V	5600	355	3,75	2610	2560	
Optional	45152-A1700	Extension 500 mm (work depth + 500 mm) to the front incl. casing for type A1700							
	45152-A2500	Extension 500 mm (work depth + 500 mm) to the front incl. casing for type A2500							
	45019	Electrical connection complete with plug and motor protection switch							
	5125039 5135539	Exhaust air damper, stage less adjustment of exhaust air volume					A1700: Ø 250 mm A2500: Ø 355 mm		
	51250-Set03 51355-Set03	Duct connection set: 3 m flexible hose (useable for solvent vapours), jalousie damper, collar and flange.					A1700: Ø 250 mm A2500: Ø 355 mm		
	79200-WE-1-258	Integration lamp for A1700/A2500, 2 x 58 = 116 Watt, steel casing and 6 mm safety glass for ex zone 2 (L x W) 1640 x 320 mm							
	45004	Turn table Ø 300 mm, for set up on the gratings							
	60120-085	Paint arrester fitting type A1700/A2500, package with 10 m²							
	61R-3-20x0,85	Dust filter set green for type A1700/A2500, roll with 17 m²							

Other types/sizes and accessories are available upon request. Our technical support service is available for further information.